



BPT 300 AUT (300x300 mm)

BPT 600 AUT (600x600 mm)

BPT 900 AUT (900x900 mm)

Braccio portatorcia ad azionamento pneumatico per processo MIG/TIG, idoneo per i modelli SPS

Pneumatically actuated torch arm for MIG/TIG welding suitable for SPS models

Пневматический держатель горелки для MIG/TIG сварки, подходит для SPS

Bras porte torche pneumatique pour MIG/TIG pour les modèles SPS

Pneumatischer Brennerhalter zum MIG/WIG Schweißen für die Modelle SPS

Brazo portasoplete de accionamiento neumático para proceso MIG/TIG. Apto para los modelos SPS



BPT 300 LINEAR [(300+150)x300 mm]

BPT 600 LINEAR [(600+150)x600 mm]

BPT 900 LINEAR [(900+150)x900 mm]

Braccio portatorcia ad azionamento pneumatico per processo MIG/TIG, idoneo per i modelli SPS. Linear 150 mm.

Pneumatically actuated torch arm for MIG/TIG welding suitable for SPS models. Linear 150 mm.

Пневматический держатель горелки для MIG/TIG сварки, подходит для SPS. Linear 150 mm.

Bras porte torche pneumatique pour MIG/TIG pour les modèles SPS. Linear 150 mm.

Pneumatischer Brennerhalter zum MIG/WIG Schweißen für die Modelle SPS. Linear 150 mm.

Brazo portasoplete de accionamiento neumático para proceso MIG/TIG. Apto para los modelos SPS. Linear 150 mm.

SPS ACCESSORI

SPS ACCESSORIES
SPS ДОПОЛНИТЕЛЬНЫЕ ПРИНАДЛЕЖНОСТИ
SPS OPTIONS
SPS ZUBEHÖR
SPS ACCESORIOS

MANINA Porta torcia

Sistema porta torcia snodabile.
Flexible torch clamping system.
Гибкий держатель с системой зажима.
Système porte torche flexible.
Brennerarmsystem mit Gelenk.
Sistema porte torche flexible.



SPS/SCH

Schermatura alta frequenza HF
High frequency (HF) shielding
защита от HF –напряжения
Protection haute fréquence HF
Hochfrequenzabschirmung HF
Protección alta frecuencia HF

SML 50x50

Slitta a croce con regolazione manuale, corsa 50x50 mm
Cross slide with manual adjustment, stroke 50x50 mm
Двухосевой суппорт с ручным регулированием, с ходом 50x50 мм
Glissière croisée avec réglage manuelle, corse 50x50 mm
Kreuz- Brennerverstellung, Regulierung manuell
Carros en cruz con regulación manual, carrera 50x50 mm





SPS/VL

Visualizzatore a LCD
LCD display
Дисплей LCD
Afficheur LCD
LCD-Display
Visualizador de LCD



CTP

Contropunta ad azionamento pneumatico corsa 600 mm
Pneumatically actuated tail stock 600 mm stroke
Пневматическая задняя бабка с ходом 600 мм
Contre pointe pneumatique course 600 mm
Pneumatische Werkstückhalterung Regulierung 600 mm
Contrapunta de accionamiento neumático carrera 600 mm



SPS/PMB

Pedale accelerazione con cavo mt. 5
Accelerator pedal with 5 mt. Cable
Педаль - регулятор скорости вращения с кабелем длиной 5 м
Pédale accélérateur avec cable mt. 5
Fusspedal mit Geschwindigkeitsregulierung und 5 mt Kabel
Pedal aceleración con cable 5 mt.